


Central Article Code: C67030D06-A
 Local Code:

Created: 02/09/2005
 Modified: 15/12/2020



Final Outlook	C6706-A
Approval date	15/01/2011

PERFORMANCES

Voltage (V):	12 V	
C20 (Ah):	28.0	10 h
Cranking (A):	280	EN
Charge:	DRY	
Technology:	Vented/Flooded	
Grid:	Low Sb	

STD. DIMENSIONS

Length (mm ± 2):	185
Width (mm ± 2):	125
Height (mm ± 2):	175

This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users
 All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

CONTAINER

Type:	C67	WHITE
Hold Down:	B0	
H.D. Adapter:	No	

COVER

Type:	Motorbike (Top ventil BLACK)
Polarity:	ETN 0
Terminals:	M11
Terminal Adapter:	No
SOCI:	No
Ventilation:	Moto-A
Filter:	No
Lateral Plug:	No

PLUGS

Type:	6 x Moto Plug	RED
-------	---------------	-----

HANDLES

Type:	None
-------	------

OTHERS

Degassing Tube:	No
-----------------	----