


## **CUSTOMER DATASHEET**


Printed: 08/11/2023


**Product Management** Transportation Europe

B24039C44-A Created: 24/02/2020 Central Article Code:


10/01/2023 Modified: Local Code: EA456







Ring Adaptors



**Final Outlook** B2444-A Approval date 15/02/2021

PERFORMANCES		CONTAINER	
Voltage (V): C20 (Ah):	12 V 45.0 20 h	Type: Hold Down:	B24 BLACK B1
Cranking (A):	390 EN	H.D. Adapter:	No
Charge:	WET		COVER
Technology:	Vented/Flooded	Type:	Double with Integrat BLACK
Grid:	Ca/Ca	Polarity:	ETN 0
Vibration:	V1 (30Hz+/-2Hz/3g/2h)	Terminals:	JIS taper post
Endurance:	E1 (180 cycles@25%)	Terminal Adapter: SOCI: Ventilation:	From JIS to EN (Ring adapter) No Central
STD. DIMENSIONS		Filter:	2 Filters
Length (mm ± 2):	237	Lateral Plug:	No
Width (mm ± 2):	127		PLUGS
Height (mm ± 2):	227	Type: 1 x Vent S	ealed (JIS) BLACK
Total Weight (kg ± 5%):	11.80	HANDLES	
		Type: 1 x Integra	ated BLACK
			OTHERS
		Degassing Tube:	No
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.			

C.O. from B24039C01-A (Grey to Black)