


CUSTOMER DATASHEET


Printed: 08/11/2023


Product Management
Transportation Europe

Central Article Code: D23058C29-A Created: 24/02/2020

Local Code: EA654 Modified: 10/01/2023







Final Outlook D2329-A Approval date 01/04/2021

PERFORMANCES

Voltage (V): 12 V

C20 (Ah): 65.0 20 h Cranking (A): 580 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

Vibration: V1 (30Hz+/-2Hz/3g/2h)

Endurance: E1 (180 cycles@25%)

STD. DIMENSIONS

 Length (mm \pm 2):
 230

 Width (mm \pm 2):
 173

 Height (mm \pm 2):
 222

 Total Weight (kg \pm 5%):
 16.00

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

Type: D23 BLACK

Hold Down: Korean B1

H.D. Adapter: No

COVER

CONTAINER

Type: Double with Integrat BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI: No Ventilation: Central

Filter: 2 Filters

Lateral Plug: No

PLUGS

Type: 1 x Vent Sealed (JIS) BLACK

HANDLES

Type: 1 x Integrated BLACK

OTHERS

Degassing Tube: No

C.O. from D23058C05-A (Grey to Black)