


Central Article Code: LB4080C10-C
 Local Code: EA852

Created: 24/02/2020
 Modified: 06/11/2023



PERFORMANCES

Voltage (V):	12 V
C20 (Ah):	85.0 20 h
Cranking (A):	800 EN
Charge:	WET
Technology:	Vented/Flooded
Grid:	Ca/Ca
Vibration:	V1 (30Hz+/-2Hz/3g/2h)
Endurance:	E2 (90 cycles@50%)

STD. DIMENSIONS

Length (mm ± 2):	315
Width (mm ± 2):	175
Height (mm ± 2):	175
Total Weight (kg ± 5%):	18.60

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

CONTAINER

Type:	LB4	BLACK
Hold Down:	B13	
H.D. Adapter:	No	

COVER

Type:	Double with Integrat	BLACK
Polarity:	ETN 0	
Terminals:	EN taper post	
Terminal Adapter:	No	
SOCI:	No	
Ventilation:	Central	
Filter:	2 Filters	
Lateral Plug:	Standard	Left side BLACK shape

PLUGS

Type:	1 x Vent Sealed PSL-OE ha	BLACK
-------	---------------------------	-------

HANDLES

Type:	2 x PSL OE Integrated	BLACK
-------	-----------------------	-------

OTHERS

Degassing Tube:	No
-----------------	----

C.O. from LB4080C09-A (PSL-AM to PSL-OE)