


CUSTOMER DATASHEET


Printed: 08/11/2023


Product Management Transportation Europe

D31080C42-A 24/02/2020 Central Article Code: Created:

Modified: 10/01/2023 Local Code: EA954







Final Outlook D3142-A Approval date 15/02/2021

		D		\frown		N/	IA	N I			c
_	ᆮ	К	г١	u	К	IV	IA	IN	u	ᆮ	J

Voltage (V): 12 V

C20 (Ah): 95.0 20 h 800 ΕN Cranking (A):

WET Charge:

Vented/Flooded Technology:

Grid: Ca/Ca

Vibration: V1 (30Hz+/-2Hz/3g/2h)

Endurance: E1 (180 cycles@25%)

D31 **BLACK** Type:

Korean B1 Hold Down:

H.D. Adapter: No

COVER

CONTAINER

Type: Double with Integrat BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI: No Ventilation: Central 2 Filters Filter:

Lateral Plug: No

STD. DIMENSIONS

Length (mm ± 2): 306 Width $(mm \pm 2)$: 173 Height (mm ± 2): 222

PLUGS

1 x Vent Sealed (JIS) BLACK Type:

HANDLES

1 x Integrated **BLACK** Type:

OTHERS

Degassing Tube: No

C.O. from D31080C11-A (Grey to Black)

Total Weight (kg ± 5%): 21.40

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.