


CUSTOMER DATASHEET


Printed: 08/11/2023


Product Management
Transportation Europe

Central Article Code: D06130C17-A Created: 16/05/2012

Local Code: EF2353 Modified: 10/01/2023







Final Outlook D0617-A Approval date 15/05/2012

| | _ | | | $\overline{}$ | | | | | | | _ | _ |
|---|---|---|---|---------------|---|---|----|-----|---|-----|---|---|
| _ | _ | ĸ | - | | R | w | ΙД | N | и | -51 | _ | • |
| | _ | | | _ | | | _ | v v | | _ | _ | • |

Voltage (V): 12 V

C20 (Ah): 235.0 20 h Cranking (A): 1300 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: E3 (144 cycles@50%)

CONTAINER

Type: D06 GREY MEDIUM Hold Down: B0

H.D. Adapter: No

COVER

Type: Flat/Press GREY MEDIUM

Polarity: ETN 3

Terminals: EN taper post

Terminal Adapter: No SOCI: No Ventilation: Central

Filter: 1 Filter per Vent

Lateral Plug: No

STD. DIMENSIONS

Length (mm ± 2): 518
Width (mm ± 2): 274
Height (mm ± 2): 240
Total Weight (kg ± 5%): 56.30

PLUGS

Type: 2 x VCL Vent GREY MEDIUM

HANDLES

Type: 2 x Rope (Rigid holder) BLACK

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.