


CUSTOMER DATASHEET


Printed: 09/11/2023


Product Management Transportation Europe

D06103G09-A Created: 06/09/2005 Central Article Code:

ES2400 Modified: 20/07/2023 Local Code:







Final Outlook D0609-A Approval date 15/06/2013

	\Box	\sim	BA A	N 1 4	\sim \sim \sim
PF	ĸF	UK	MA	N	

Voltage (V): 12 V

C20 (Ah): 210.0 20 h ΕN Cranking (A):

CHARGED Charge:

Technology: **GEL** Grid:

Ca/Ca

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: 200 cycles@100%

CONTAINER

D06 **BLACK** Type:

B0 Hold Down: H.D. Adapter: No

COVER

Type: Flat/Screw BLACK

Polarity: ETN 3

Terminals: EN taper post

Terminal Adapter: No SOCI:

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

Length (mm ± 2): 518 Width $(mm \pm 2)$: 274 Height (mm ± 2): 240 Total Weight (kg ± 5%): 63.50

PLUGS

6 x M18 Valve **GREY MEDIUM** Type:

HANDLES

2 x Rope (Rigid holder) BLACK Type:

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

DNV-GL type approved 2015/Used for Bosch