


Central Article Code: LB1028G19-A
 Local Code: ES450

Created: 06/09/2005
 Modified: 20/07/2023



Final Outlook	LB119-A
Approval date	15/08/2011

PERFORMANCES

Voltage (V):	12 V
C20 (Ah):	40.0 20 h
Cranking (A):	0 EN
Charge:	CHARGED
Technology:	GEL
Grid:	Ca/Ca
Vibration:	V3 (30Hz+/-2Hz/6g/20h)
Endurance:	200 cycles@100%

STD. DIMENSIONS

Length (mm ± 2):	207
Width (mm ± 2):	175
Height (mm ± 2):	175
Total Weight (kg ± 5%):	14.20

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

CONTAINER

Type:	LB1	BLACK
Hold Down:	B4	
H.D. Adapter:	No	

COVER

Type:	DIN	BLACK
Polarity:	ETN 0	
Terminals:	EN full Ford lug	
Terminal Adapter:	No	
SOCI:	No	
Ventilation:	Independent	
Filter:	No	
Lateral Plug:	No	

PLUGS

Type:	6 x M18 Valve	GREY MEDIUM
-------	---------------	-------------

HANDLES

Type:	None
-------	------

OTHERS

Degassing Tube:	No
-----------------	----

DNV-GL type approved 2015/Used for Bosch