


## **CUSTOMER DATASHEET**


Printed: 17/05/2021


Product Management
Transportation Europe

Central Article Code: C54012F01-A Created: 26/10/2006

Local Code: Modified: 15/12/2020







Final Outlook C5401-A Approval date 01/12/2009

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	C54	BLACK
C20 (Ah):	8.0	10 h	Hold Down:	B0	
Cranking (A):	120	EN	H.D. Adapter:	No	
Charge:	DRY		COVER		
Technology:	AGM		Type:	Motorbik	e (independ BLACK
Grid:	Ca/Ca		Polarity:	ETN 1	
			Terminals:	M12	
			Terminal Adapter:	No	
			SOCI:	No	
			Ventilation:	Sealed	
STD. DIMENSIONS			Filter:	No	
Length (mm ± 2):	150		Lateral Plug:	No	
Width (mm ± 2):	90		PLUGS		
Height (mm ± 2):	105		Type: 1 x Vent		BLACK
				HANDLES	
			Type: None		
			OTHERS		
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users			Degassing Tube:	No	
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.					